

# UCP Expression

A custom fit active wheelchair for image-conscious users in urban and semi-urban areas who are economically disadvantaged. Chair features light weight, super durability, transportability, extensive fit and positioning options, and a sleek urban look. Carries CE mark. Manufactured in factory with ISO 9000 quality system.



- Sweeping frame curves have sleek urban look similar to expensive chairs in the USA.
- Lighter weight than standard wheelchairs or rough terrain chairs for easy pushing.
- Versatile with a small footprint for maneuverability in tight places and speedy wheels on pavement and off. Works well in the office, local park, and on camping trips and traveling.
- Quick release wheels make chair easily transportable in cars.
- Designed in the USA by UCP, an international NGO committed to the advancement of wheelchair users worldwide.
- Strong enough for challenging environments. Durable bearings, wheels, and casters in standard easy-to-replace sizes. Strong enough to go up and down curbs every day.
- The best blend of style, affordability, and fit available today anywhere in the world.



Adjustability



Sleek curved design



Fold down back



Durability



**\$235 USD per unit for LCL or FCL orders. Delivery time is 3 weeks or less.**

	Small frame		Medium frame		Long Frame	
<b>Seat width</b>	315mm (12 3/8")	355mm (14")	355mm (14")	395mm (15 1/2")	430mm (17")	470mm (18 1/2")
<b>Seat depth</b>	250mm–350mm (9 3/4"–13 3/4")		330mm (13")–430mm (17")		405mm (16")–505mm (19 7/8")	
<b>Front seat height</b>	420mm (16.5")–450mm (17 3/4")		440mm (17 3/8")–470mm (18 1/2")		480mm (18 7/8")–510mm (20")	
<b>Seat angle from ground</b>	4"		6"			
<b>Backrest height</b>	280 (11")–360 (14 1/8")		280 (11")–360 (14 1/8")	360 (14 1/8")–440 (17 3/8")		
<b>Backrest angle from seat sling</b>	80°–120°					
<b>Footrest height</b>	200–280mm (7 7/8"–11")	260–340mm (10 1/4"–13 3/8")	260–360mm (10 1/4"–14 1/8")	330–410mm (13"–16 1/8")		
<b>Rear wheel camber angle</b>	4"					
<b>Overall width</b>	585mm (23")	625mm (24 5/8")	625mm (24 5/8")	665mm (26 1/8")	700mm (27 1/2")	740mm (29 1/8")

